

**CHARNOCK INITIAL
REGIONAL RESPONSE ACTIVITIES (CIRRA)
Charnock Sub-Basin; Los Angeles, California
Task 14 Interim Restoration Measures**

**Analysis of the Performance of the Sepulveda-Venice
Subregional Groundwater Remediation
Systems**

Submitted to:

California Regional Water Quality Control Board,
Los Angeles Region

U.S. Environmental Protection Agency,
Region IX

On behalf of:

Shell Oil Company
Shell Oil Products Company
Equilon Enterprises LLC

Prepared by:

ENVIRON Corporation
Emeryville, California

January 7, 2002
03-89800

TABLE OF CONTENTS

1.0	Introduction	1-1
2.0	Conceptual Model of Historic Gasoline Migration	2-1
2.1	Hydrogeology of the Sepulveda-Venice Subregion.....	2-1
2.2	Historic Groundwater Remediation Activities.....	2-2
2.3	Gasoline Constituent Concentrations in Groundwater.....	2-4
2.4	Characterization of Gasoline Residuum in the Sepulveda-Venice Subregion.....	2-5
2.5	Subregional Groundwater Remediation Goals.....	2-7
3.0	Predictive Models of MTBE Dissolution.....	3-1
4.0	Estimation of Pore Volume Flushing in the Sepulveda-Venice Subregion.....	4-1
4.1	Conceptual Approach.....	4-1
4.2	Groundwater Flushing Scenarios	4-2
4.3	Estimation of Pore Volume Flushing.....	4-3
5.0	Analysis and Discussion.....	5-1
6.0	References	6-1

LIST OF TABLES

Table 2-1	Summary of Core Analysis Results from B-22A
Table 2-2	Soil Sampling Results from MW-22S
Table 2-3	Groundwater Sampling Results from MW-22S
Table 4-1	Remedial Pumping Rates from Sepulveda-Venice Sub-Region Through 2001
Table 4-2	Assumed Pumping Rates for Sepulveda-Venice Remedial Wells for 2002-2010
Table 5-1	Pore Volumes Flushed at Intersection of I-405 and Venice Boulevard by January 2010

LIST OF FIGURES

Figure 1-1	Location of Extraction Wells in Sepulveda-Venice Sub-Region
Figure 1-2	Top of Shallow Aquitard
Figure 1-3	Potentiometric Surface Map – Shallow Aquifer, April 2001
Figure 1-4	Potentiometric Surface Map – Upper Silverado Aquifer, April 2001
Figure 1-5	Third Quarter, 2001 MTBE and TPH Concentration – Shallow Aquifer
Figure 1-6	Third Quarter, 2001 MTBE and TPH Concentration – Upper Silverado Aquifer
Figure 2-1	Abrams Shell Site Radius of Influence for SVE Wells
Figure 3-1	Dissolution Curves From a Model Gasoline in Soil

LIST OF FIGURES (cont.)

Alternative 1A1 (Nominal S-V Pumping)

- Figure 4-1 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2002
- Figure 4-2 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2005
- Figure 4-3 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2010

Alternative 1A1 (Eastern S-V Pumping)

- Figure 4-4 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2005
- Figure 4-5 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2010

Alternative 1A1 (Western S-V Injection)

- Figure 4-6 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2005
- Figure 4-7 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2010

Alternative 1A1 (Higher S-V Pumping)

- Figure 4-8 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2005
- Figure 4-9 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2010

Recommended Response Alternative (Nominal S-V Pumping)

- Figure 4-10 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2002
- Figure 4-11 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2005
- Figure 4-12 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2010

Recommended Response Alternative (Eastern S-V Pumping)

- Figure 4-13 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2005
- Figure 4-14 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2010

Recommended Response Alternative (Western S-V Injection)

- Figure 4-15 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2005
- Figure 4-16 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2010

Recommended Response Alternative (Higher S-V Pumping)

- Figure 4-17 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2005
- Figure 4-18 Pore Volumes Flushed in Shallow Aquifer Through 1-Jan-2010

Recommended Response Alternative (Nominal S-V Pumping)

- Figure 4-19 Pore Volumes Flushed in Upper Silverado Through 1-Jan-2002
- Figure 4-20 Pore Volumes Flushed in Upper Silverado Through 1-Jan-2005
- Figure 4-21 Pore Volumes Flushed in Upper Silverado Through 1-Jan-2010

LIST OF APPENDICES

- Appendix A Dissolution of MTBE From a Residually Trapped Gasoline Source, A Summary of Research Results by William G. Rixey and Sushrut Joshi, University of Houston

1.0 INTRODUCTION

This report has been prepared by ENVIRON International Corporation on behalf of Shell Oil Company, Shell Oil Products Company, and Equilon Enterprises LLC (Shell) in partial fulfillment of the work required by Task 14 of Attachment A-Scope of Work (SOW) to the Los Angeles Regional Water Quality Control Board (LARWQCB) and the United States Environmental Protection Agency (USEPA) (herein collectively referred to as the “Agencies”) under Stipulated Agreement No. 00-064 and the Administrative Order on Consent, USEPA Docket No. RCRA 7003-09-2000-0003 (SA/AOC). The scope of the analyses presented in this report has been further defined in a letter to Shell from the Agencies dated August 13, 2001, and a letter of reply from ENVIRON dated September 10, 2001.

The purpose of the analyses presented in this report is to evaluate the effectiveness of the current ground water remediation systems operated by Shell and Exxon-Mobil in reducing the mass of gasoline residuum¹ and related soluble gasoline constituents, which have affected ground water quality in the Sepulveda-Venice subregion of the Charnock Sub-Basin. Based on these analyses, a forecast of the future progress in further reducing constituent concentrations in the Shallow and Upper Silverado aquifers is presented.

¹ Gasoline residuum is residual non-aqueous phase gasoline trapped in the pores of saturated soils below the water table.